



SnoMaster®



SnoMaster

PRODUCT CATALOGUE

ISSUE : 3

2 0 2 5 - 2 0 2 6



Since 2002, SnoMaster® has been synonymous with luxury, quality, and reliability. Our cutting-edge technology and sophisticated designs create exceptional products that elevate our customers' lifestyles. Our extensive range of beverage coolers, wine coolers, ice-makers, and water dispensers blend technological precision with design elegance to perfectly fit your lifestyle. Whether for your apartment, home, office, or hospitality business, SnoMaster® offers seamless integration with uninterrupted, low-maintenance, high-capacity operation. Discover the perfect solution for any setting with SnoMaster®.



JOHANNESBURG LIFESTYLE CENTRE & SERVICE CENTRE

49 Koornhof Road, Meadowdale
Germiston, 1614

011 392 5315 / 3147

info@snomaster.co.za



CAPE TOWN LIFESTYLE CENTRE & SERVICE CENTRE

31 Stella Road, Montague Gardens
Cape Town, 7441

021 100 5695

info@snomaster.co.za



@SnoMasterSA



SnoMaster SA



snomaster_south_africa



@SnoMaster



@snomastersa

CONT

03

MOBILE FRIDGES & FREEZERS



EXPEDITION SERIES

17

MOBILE FRIDGES & FREEZERS



SMEX RANGE

25

MOBILE FRIDGES & FREEZERS



LEISURE SERIES

31

MISCELLANEOUS



12V ACCESSORIES

35

WARRANTY



WARRANTY INFORMATION

ENTS



MOBILE FRIDGES & FREEZERS

BUILT FOR THE JOURNEY. READY WHEN YOU ARE

The SnoMaster Expedition Series is made for those who go further, whether it's off the grid or just off the beaten track. Designed for serious adventure, these Mobile Fridges & Freezers combine durable stainless steel construction with reliable cooling power to handle tough terrain and long days on the road.

With single or dual compartments, metal baskets, heavy duty transit covers and flexible power options, they are as versatile as your next trip. Whether you are chasing the horizon or setting up camp, the Expedition Series keeps your supplies cold and your adventure on track.



Dimensions (mm) Unit:
(H) 520 (W) 625 (D) 460



Storage Volume:
40L



Temp Range:
-22°C to 10°C



Net Weight:
24Kg



Compressor:
45W



Rated Current:
12V: **3.75A**
220V: **0.42A**



Cyclopentane Insulation:
60mm



Voltage:
AC: **230V/50Hz**
DC: **12V/24V**

SMDZ-CL40

**40L SINGLE COMPARTMENT
MOBILE FRIDGE & FREEZER AC/DC
STAINLESS STEEL**

PRODUCT FEATURES

- ✓ Single Compartment
- ✓ 3-Speed Setting – High, Auto & Low
- ✓ SnoMaster® Compressor
- ✓ Interchangeable Temperature Controller
- ✓ Low-Voltage Cut-Out Setting (10, 10.7, 11.8V)
- ✓ Corner Feet with Mounting Holes
- ✓ Secure Mini Anderson Input & Output Plugs
- ✓ Internal LED Light
- ✓ Removable/Reversible Lid (Sliding Hinges)
- ✓ Lid-Open Alarm
- ✓ Stainless Steel Hinges, Locks and Handles
- ✓ Includes: Baskets, Bottle Opener, Solar-Powered Remote Control and Transit Cover
- ✓ Designed For African Conditions



SCAN FOR MORE INFO



PLEASE NOTE:

All dimensions include handles and hinges. Maintain a 150mm clearance around the unit, ensuring adequate air circulation. Avoid tilting the appliance more than 45 degrees from its upright position.

1-YEAR WARRANTY ON PARTS NOT LISTED

SMDZ-TR42S

**42L SINGLE COMPARTMENT
MOBILE FRIDGE & FREEZER AC/DC
STAINLESS STEEL**



05



Dimensions (mm) Unit:
(H) 520 (W) 365 (D) 680



Storage Volume:
42L



Temp Range:
-22°C to 10°C



Net Weight:
23.5Kg



Compressor:
45W



Rated Current:
12V: 3.75A
220V: 0.42A



Polyurethane Insulation:
50mm



Voltage:
AC: 230V/50Hz
DC: 12V/24V

- ✓ Single Compartment
- ✓ 3-Speed Setting – High, Auto & Low
- ✓ SnoMaster® Compressor
- ✓ Low-Voltage Cut-Out Setting (10, 10.7, 11.8V)
- ✓ Corner Feet with Mounting Holes
- ✓ Secure Mini Anderson Input & Output Plugs
- ✓ Internal LED Light
- ✓ Fixed Hinged Lid
- ✓ Lid-Open Alarm
- ✓ Stainless Steel Hinges, Locks and Handles
- ✓ Includes: Baskets, Bottle Opener, Solar-Powered Remote Control and Transit Cover
- ✓ Designed For African Conditions

PRODUCT FEATURES

PLEASE NOTE:

All dimensions include handles and hinges. Maintain a 150mm clearance around the unit, ensuring adequate air circulation. Avoid tilting the appliance more than 45 degrees from its upright position.

1-YEAR WARRANTY ON PARTS NOT LISTED



SCAN FOR MORE INFO



Dimensions (mm) Unit:
(H) 515 (W) 755 (D) 500



Storage Volume: **56L**
Left: **26L**
Right: **30L**



Temp Range:
-22°C to 10°C



Net Weight:
28Kg



Compressor:
70W



Rated Current:
12V: **5.92A**
220V: **0.52A**



Polyurethane Insulation:
60mm



Voltage:
AC: **230V/50Hz**
DC: **12V/24V**

SMDZ-CL56D

**56L DUAL COMPARTMENT
MOBILE FRIDGE & FREEZER AC/DC
STAINLESS STEEL**

PRODUCT FEATURES

- ✓ Dual Compartment
- ✓ 3-Speed Setting – High, Auto & Low
- ✓ SnoMaster® Compressor
- ✓ Interchangeable Temperature Controller
- ✓ Low-Voltage Cut-Out Setting (10, 10.7, 11.8V)
- ✓ Corner Feet with Mounting Holes
- ✓ Secure Mini Anderson Input & Output Plugs
- ✓ Internal LED Light
- ✓ Removable Lid (Sliding Hinges)
- ✓ Lid-Open Alarm
- ✓ Stainless Steel Hinges, Locks and Handles
- ✓ Includes: Baskets, Bottle Opener, Solar-Powered Remote Control and Transit Cover
- ✓ Designed For African Conditions



SCAN FOR MORE INFO



PLEASE NOTE:

All dimensions include handles and hinges. Maintain a 150mm clearance around the unit, ensuring adequate air circulation. Avoid tilting the appliance more than 45 degrees from its upright position.

1-YEAR WARRANTY ON PARTS NOT LISTED

06

SMDZ-CL60

**60L SINGLE COMPARTMENT
MOBILE FRIDGE & FREEZER AC/DC
STAINLESS STEEL**



07

	Dimensions (mm) Unit: (H) 515 (W) 755 (D) 495		Compressor: 70W
	Storage Volume: 60L		Rated Current: 12V: 5.92A 220V: 0.52A
	Temp Range: -22°C to 10°C		Polyurethane Insulation: 60mm
	Net Weight: 26Kg		Voltage: AC: 230V/50Hz DC: 12V/24V

- ✓ Single Compartment
- ✓ 3-Speed Setting – High, Auto & Low
- ✓ SnoMaster® Compressor
- ✓ Interchangeable Temperature Controller
- ✓ Low-Voltage Cut-Out Setting (10, 10.7, 11.8V)
- ✓ Corner Feet with Mounting Holes
- ✓ Secure Mini Anderson Input & Output Plugs
- ✓ Internal LED Light
- ✓ Removable Lid (Sliding Hinges)
- ✓ Lid-Open Alarm
- ✓ Stainless Steel Hinges, Locks and Handles
- ✓ Includes: Baskets, Bottle Opener, Solar-Powered Remote Control and Transit Cover
- ✓ Designed For African Conditions

PRODUCT FEATURES

PLEASE NOTE:
All dimensions include handles and hinges. Maintain a 150mm clearance around the unit, ensuring adequate air circulation. Avoid tilting the appliance more than 45 degrees from its upright position.

1-YEAR WARRANTY ON PARTS NOT LISTED



SCAN FOR MORE INFO



Dimensions (mm) Unit:
(H) 450 (W) 770 (D) 580



Storage Volume:
65L



Temp Range:
-22°C to 10°C



Net Weight:
31.5Kg



Compressor:
70W



Rated Current:
12V: **5.92A**
220V: **0.52A**



Polyurethane Insulation:
60mm



Voltage:
AC: **230V/50Hz**
DC: **12V/24V**

SMDZ-LP65

**65L LOW PROFILE SINGLE COMPARTMENT
MOBILE FRIDGE & FREEZER AC/DC
STAINLESS STEEL**

PRODUCT FEATURES

- ✓ Low Profile
- ✓ Single Compartment
- ✓ 3-Speed Setting – High, Auto & Low
- ✓ SnoMaster® Compressor
- ✓ Interchangeable Temperature Controller
- ✓ Low-Voltage Cut-Out Setting (10, 10.7, 11.8V)
- ✓ Corner Feet with Mounting Holes
- ✓ Secure Mini Anderson Input & Output Plugs
- ✓ Internal LED Light
- ✓ Removable Lid (Sliding Hinges)
- ✓ Lid-Open Alarm
- ✓ Stainless Steel Hinges, Locks and Handles
- ✓ Includes: Baskets, Bottle Opener, Solar-Powered Remote Control and Transit Cover
- ✓ Designed For African Conditions



SCAN FOR MORE INFO



PLEASE NOTE:

All dimensions include handles and hinges. Maintain a 150mm clearance around the unit, ensuring adequate air circulation. Avoid tilting the appliance more than 45 degrees from its upright position.

1-YEAR WARRANTY ON PARTS NOT LISTED

08





Dimensions (mm) Unit:
(H) 470 (W) 845 (D) 520



Storage Volume: **66L**
Left: **32.5L**
Right: **33.5L**



Temp Range:
-22°C to 10°C



Net Weight:
28Kg



Compressor:
70W



Rated Current:
12V: **5.92A**
220V: **0.52A**



Polyurethane Insulation:
60mm



Voltage:
AC: **230V/50Hz**
DC: **12V/24V**

SMDZ-LP66D

**66L LOW PROFILE DUAL COMPARTMENT
MOBILE FRIDGE & FREEZER AC/DC
STAINLESS STEEL**



PRODUCT FEATURES

- ✓ Low Profile
- ✓ Dual Compartment
- ✓ 3-Speed Setting – High, Auto & Low
- ✓ SnoMaster® Compressor
- ✓ Interchangeable Temperature Controller
- ✓ Low-Voltage Cut-Out Setting (10, 10.7, 11.8V)
- ✓ Corner Feet with Mounting Holes
- ✓ Secure Mini Anderson Input & Output Plugs
- ✓ Internal LED Light
- ✓ Removable Lid (Sliding Hinges)
- ✓ Lid-Open Alarm
- ✓ Stainless Steel Hinges, Locks and Handles
- ✓ Includes: Baskets, Bottle Opener, Solar-Powered Remote Control and Transit Cover
- ✓ Designed For African Conditions



SCAN FOR MORE INFO



PLEASE NOTE:

All dimensions include handles and hinges. Maintain a 150mm clearance around the unit, ensuring adequate air circulation. Avoid tilting the appliance more than 45 degrees from its upright position.

1-YEAR WARRANTY ON PARTS NOT LISTED

10

SMDZ-EX67D

**66L DUAL COMPARTMENT
MOBILE FRIDGE & FREEZER AC/DC
STAINLESS STEEL**



11



Dimensions (mm) Unit:
(H) 530 (W) 840 (D) 520



Storage Volume: 66L
Left: **30L**
Right: **36L**



Temp Range:
-22°C to 10°C



Net Weight:
32Kg



Compressor:
70W



Rated Current:
12V: **5.92A**
220V: **0.52A**



Polyurethane Insulation:
70mm



Voltage:
AC: **230V/50Hz**
DC: **12V/24V**

- ✓ Dual Compartment
- ✓ 3-Speed Setting – High, Auto & Low
- ✓ SnoMaster® Compressor
- ✓ Interchangeable Temperature Controller
- ✓ Low-Voltage Cut-Out Setting (10, 10.7, 11.8V)
- ✓ Corner Feet with Mounting Holes
- ✓ Secure Mini Anderson Input & Output Plugs
- ✓ Internal LED Light
- ✓ Removable Lid (Sliding Hinges)
- ✓ Lid-Open Alarm
- ✓ Stainless Steel Hinges, Locks and Handles
- ✓ Includes: Baskets, Bottle Opener, Solar-Powered Remote Control and Transit Cover
- ✓ Designed For African Conditions

PRODUCT FEATURES

PLEASE NOTE:

All dimensions include handles and hinges. Maintain a 150mm clearance around the unit, ensuring adequate air circulation. Avoid tilting the appliance more than 45 degrees from its upright position.

1-YEAR WARRANTY ON PARTS NOT LISTED



SCAN FOR MORE INFO



Dimensions (mm) Unit:
(H) 600 (W) 755 (D) 505



Storage Volume: **72L**
Left: **32L**
Right: **40L**



Temp Range:
-22°C to 10°C



Net Weight:
31.5Kg



Compressor:
70W



Rated Current:
12V: **5.92A**
220V: **0.52A**



Polyurethane Insulation:
60mm



Voltage:
AC: **230V/50Hz**
DC: **12V/24V**

SMDZ-CL72D

**72L DUAL COMPARTMENT
MOBILE FRIDGE & FREEZER AC/DC
STAINLESS STEEL**

PRODUCT FEATURES

- ✓ Dual Compartment
- ✓ 3-Speed Setting – High, Auto & Low
- ✓ SnoMaster® Compressor
- ✓ Interchangeable Temperature Controller
- ✓ Low-Voltage Cut-Out Setting (10, 10.7, 11.8V)
- ✓ Corner Feet with Mounting Holes
- ✓ Secure Mini Anderson Input & Output Plugs
- ✓ Internal LED Light
- ✓ Removable Lid (Sliding Hinges)
- ✓ Lid-Open Alarm
- ✓ Stainless Steel Hinges, Locks and Handles
- ✓ Included: Baskets, Bottle Opener, Solar-Powered Remote Control, Transit Cover
- ✓ Designed For African Conditions



SCAN FOR MORE INFO



PLEASE NOTE:

All dimensions include handles and hinges. Maintain a 150mm clearance around the unit, ensuring adequate air circulation. Avoid tilting the appliance more than 45 degrees from its upright position.

1-YEAR WARRANTY ON PARTS NOT LISTED

12

SMDZ-CL80

**80L SINGLE COMPARTMENT
MOBILE FRIDGE & FREEZER AC/DC
STAINLESS STEEL**



13



Dimensions (mm) Unit:
(H) 600 (W) 755 (D) 505



Storage Volume:
80L



Temp Range:
-22°C to 10°C



Net Weight:
30Kg



Compressor:
70W



Rated Current:
12V: 5.92A
220V: 0.52A



Polyurethane Insulation:
60mm



Voltage:
AC: 230V/50Hz
DC: 12V/24V

- ✓ Single Compartment
- ✓ 3-Speed Settings – High, Auto & Low
- ✓ SnoMaster® Compressor
- ✓ Interchangeable Temperature Controller
- ✓ Low-Voltage Cut-Out Setting (10, 10.7, 11.8V)
- ✓ Corner Feet with Mounting Holes
- ✓ Secure Mini Anderson Input & Output Plugs
- ✓ Internal LED Light
- ✓ Removable Lid (Sliding Hinges)
- ✓ Lid-Open Alarm
- ✓ Stainless Steel Hinges, Locks and Handles
- ✓ Includes: Baskets, Bottle Opener, Solar-Powered Remote Control and Transit Cover
- ✓ Designed For African Conditions

PRODUCT FEATURES

PLEASE NOTE:

All dimensions include handles and hinges. Maintain a 150mm clearance around the unit, ensuring adequate air circulation. Avoid tilting the appliance more than 45 degrees from its upright position.

1-YEAR WARRANTY ON PARTS NOT LISTED



SCAN FOR MORE INFO



Dimensions (mm) Unit:
(H) 535 (W) 840 (D) 520



Storage Volume: **81.5L**
Left: **39L**
Right: **42.5L**



Temp Range:
-22°C to 10°C



Net Weight:
35Kg



Compressor:
70W



Rated Current:
12V: **5.92A**
220V: **0.52A**



Polyurethane Insulation:
60mm



Voltage:
AC: **230V/50Hz**
DC: **12V/24V**

SMDZ-TR82D

**81.5L DUAL COMPARTMENT
MOBILE FRIDGE & FREEZER AC/DC
STAINLESS STEEL**

PRODUCT FEATURES

- ✓ Dual Compartment
- ✓ 3-Speed Settings – High, Auto & Low
- ✓ SnoMaster® Compressor
- ✓ Interchangeable Temperature Controller
- ✓ Low-Voltage Cut-Out Setting (10, 10.7, 11.8V)
- ✓ Corner Feet with Mounting Holes
- ✓ Secure Mini Anderson Input & Output Plugs
- ✓ Internal LED Light
- ✓ Removable Lid (Sliding Hinges)
- ✓ Lid-Open Alarm
- ✓ Stainless Steel Hinges, Locks and Handles
- ✓ Includes: Baskets, Bottle Opener, Solar-Powered Remote Control and Transit Cover
- ✓ Designed For African Conditions



SCAN FOR MORE INFO



PLEASE NOTE:

All dimensions include handles and hinges.
Maintain a 150mm clearance around the unit,
ensuring adequate air circulation. Avoid tilting
the appliance more than 45 degrees from its
upright position.

1-YEAR WARRANTY ON PARTS NOT LISTED

14

SMDZ-LP96D

**92.5L LOW PROFILE DUAL COMPARTMENT
MOBILE FRIDGE & FREEZER AC/DC
STAINLESS STEEL**



Dimensions (mm) Unit:
(H) 465 (W) 990 (D) 575



Storage Volume: 92.5L
Left: 41L
Right: 51.5L



Temp Range:
-22°C to 10°C



Net Weight:
39.5Kg



Compressor:
70W



Rated Current:
12V: 5.92A
220V: 0.52A



Polyurethane Insulation:
70mm



Voltage:
AC: 230V/50Hz
DC: 12V/24V

- ✓ Low Profile
- ✓ Dual Compartment
- ✓ 3-Speed Settings – High, Auto & Low
- ✓ SnoMaster® Compressor
- ✓ Interchangeable Temperature Controller
- ✓ Low-Voltage Cut-Out Setting (10, 10.7, 11.8V)
- ✓ Corner Feet with Mounting Holes
- ✓ Secure Mini Anderson Input & Output Plugs
- ✓ Internal LED Light
- ✓ Removable Lid (Sliding Hinges)
- ✓ Lid-Open Alarm
- ✓ Stainless Steel Hinges, Locks and Handles
- ✓ Includes: Baskets, Bottle Opener, Solar-Powered Remote Control and Transit Cover
- ✓ Designed For African Conditions

PRODUCT FEATURES

15

PLEASE NOTE:
All dimensions include handles and hinges.
Maintain a 150mm clearance around the unit,
ensuring adequate air circulation. Avoid tilting
the appliance more than 45 degrees from its
upright position.

1-YEAR WARRANTY ON PARTS NOT LISTED



SCAN FOR MORE INFO



SMEX

RANGE



READY WHEN YOU ARE

The SnoMaster SMEX Range of Mobile Fridges & Freezers is made for everyday escapes. Whether it is a weekend away, a day trip to the bush or just keeping drinks cold at the campsite, these appliances offer the flexibility and reliability you need to take the moment as it comes.

Tough enough for off-road use and easy enough for first-time buyers, the SMEX Range is the ideal choice for holidaymakers, adventurers and weekend explorers. With durable stainless steel construction, efficient cooling and simple controls, each Fridge & Freezer is built to handle the way you live and the way you travel.



SMEX 41S

**41L SINGLE COMPARTMENT
MOBILE FRIDGE & FREEZER STAINLESS STEEL**



Dimensions (mm) Unit:
(H) 500 (W) 364 (D) 716



Storage Volume: **41L**
65 x 300ml Beverage Cans



Temp Range:
-20°C to 10°C



Net Weight:
19.3Kg



Compressor:
65W



Rated Current:
12V: **6.75A** | 24V: **3.48A**
220V: **0.68A**



Insulation:
Cyclopentane



Voltage:
AC: **220V**
DC: **12V/24V**



SCAN FOR MORE INFO





BOTTLE OPENER
ON LID



CORNER FEET WITH
MOUNTING HOLES



INCLUDES
BASKET



AIRTIGHT
LID SEAL



INTERNAL AC/DC
POWER SUPPLY



DURABLE PLASTIC
HANDLES



INTERNAL LED
LIGHT



SOFT CLOSING
LID



DETACHABLE
LID



DIGITAL TEMPERATURE
CONTROL



SECURE LID
CLIP



DRAINAGE
OUTLET

SMEX 78D

**78L DUAL COMPARTMENT
MOBILE FRIDGE & FREEZER
STAINLESS STEEL**



Dimensions (mm) Unit:
(H) 535 (W) 875 (D) 470



Storage Volume: **78L**
Left: **34L** | Right: **44L**
117 x 300ml Beverage Cans



Temp Range:
-20°C to 10°C



Net Weight:
27.8Kg



Compressor:
80W



Rated Current:
12V: **12V: 6.92A** | 24V: **3.60A**
220V: **0.78A**



Insulation:
Cylopentane



Voltage:
AC: **220V**
DC: **12V/24V**



SCAN FOR MORE INFO





**BOTTLE OPENERS
ON LID**



**CORNER FEET WITH
MOUNTING HOLES**



**INCLUDES
2 X BASKETS**



**AIRTIGHT
LID SEAL**



**INTERNAL AC/DC
POWER SUPPLY**



**DURABLE PLASTIC
HANDLES**



**INTERNAL LED
LIGHTS**



**EMERGENCY
OVERRIDE SWITCH**



**MULTIDIRECTIONAL
LIDS (REMOVABLE)**



**DIGITAL TEMPERATURE
CONTROL**



**DURABLE
LID CLIPS**



**DRAINAGE
OUTLETS**

SMEX 98D

**98L DUAL COMPARTMENT
MOBILE FRIDGE & FREEZER AC/DC
STAINLESS STEEL**



Dimensions (mm) Unit:
(H) 465 (W) 1027 (D) 531



Storage Volume: **98L**
Left: **42.5L** | Right: **55.5L**
326 x 300ml Beverage Cans



Temp Range:
-20°C to 10°C



Net Weight:
30.5Kg



Compressor:
80W



Rated Current:
12V: **12V: 6.92A** | 24V: **3.60A**
220V: **0.78A**



Polyurethane Insulation:
60mm



Voltage:
AC: **220V**
DC: **12V/24V**



SCAN FOR MORE INFO



BOTTLE OPENERS
ON LID



CORNER FEET WITH
MOUNTING HOLES



INCLUDES
2 X BASKETS



AIRTIGHT
LID SEAL



INTERNAL AC/DC
POWER SUPPLY



DURABLE PLASTIC
HANDLES



INTERNAL LED
LIGHTS



EMERGENCY
OVERRIDE SWITCH



MULTIDIRECTIONAL
LIDS (REMOVABLE)



DIGITAL TEMPERATURE
CONTROL



DURABLE
LID CLIPS



DRAINAGE
OUTLETS



MOBILE FRIDGES AND FREEZERS

LIGHT TO CARRY. BUILT TO EXPLORE

The SnoMaster Leisure Series of Mobile Fridges & Freezers are made for weekends away, beach days, picnics and camping trips. Lightweight yet tough, these appliances feature durable plastic construction that makes them easy to move and ready for the outdoors.

Simple to use and built with the same reliable cooling performance SnoMaster is known for, they run off 12V or 24V DC and 220V AC power, giving you the freedom to plug in wherever your plans take you. With a range of sizes and features to suit every kind of trip, the Leisure Series is your go-anywhere solution for keeping things cold, fresh and ready to enjoy.



Dimensions (mm) Unit:
(H) 390 (W) 195 (D) 505



Storage Volume:
12L



Temp Range:
-12°C to 10°C



Net Weight:
8.5Kg



Compressor:
45W



Rated Current:
12V: **3.75A**
220V: **1.25A**



Cyclopentane Insulation
Polyurethane Exterior



Voltage:
12V/24V

SMDZ-LS12

**12L PLASTIC MOBILE FRIDGE
& FREEZER DC
BLACK**



PRODUCT FEATURES

- ✓ 1-Speed Setting
- ✓ On/Off Operational Switch
- ✓ USB Port
- ✓ Digital Temperature Control
- ✓ Durable Plastic
- ✓ Internal DC Power Supply (12V Only)
- ✓ Lightweight
- ✓ Low-Voltage Cut-Out Setting (10, 10.7, 11.8V)
- ✓ Interior LED Light
- ✓ Supplied with Mounting Bracket and Carry Straps
- ✓ Designed For African Conditions



SCAN FOR MORE INFO



PLEASE NOTE:

All dimensions include handles and hinges.
Maintain a 150mm clearance around the unit,
ensuring adequate air circulation. Avoid tilting
the appliance more than 45 degrees from its
upright position.

1-YEAR WARRANTY ON PARTS NOT LISTED

26

SMLS-38

**36.5L PLASTIC MOBILE FRIDGE &
FREEZER DC WITH 220V POWER ADAPTER
GREY**

 Dimensions (mm) Unit: (H) 465 (W) 616 (D) 382	 Compressor: 55W
 Storage Volume: 36.5L	 Rated Current: 12V: 4.58A 220V: 0.395A
 Temp Range: -20°C to 10°C	 Insulation: Cyclopentane
 Net Weight: 14.3Kg	 Voltage: 12V/24V With 220V External AC Adapter



- ✓ Lightweight
- ✓ Shockproof Design
- ✓ Durable Plastic Handles
- ✓ Digital Temperature Controller
- ✓ Internal DC Power Supply (With 220V External AC Power Adapter)
- ✓ 2 Bottle Openers
- ✓ Cupholders On Lid
- ✓ Secure Carry Points
- ✓ Internal LED Light
- ✓ 2-Speed Setting - Turbo & Eco
- ✓ Low-Voltage Cut-Out Settings (10, 10.7, 11.8V)
- ✓ Compartment Divider (Small Compartment 5°C - 7°C Variance)
- ✓ Designed For African Conditions

PRODUCT FEATURES

PLEASE NOTE:
All dimensions include handles and hinges. Maintain a 150mm clearance around the unit, ensuring adequate air circulation. Avoid tilting the appliance more than 45 degrees from its upright position.

1-YEAR WARRANTY ON PARTS NOT LISTED





Dimensions (mm) Unit:
(H) 543 (W) 702 (D) 420



Storage Volume:
54L



Temp Range:
-20°C to 10°C



Net Weight:
16.5kg



Compressor:
55W



Rated Current:
12V: **4.58A**
220V: **0.395A**



Insulation:
Cyclopentane



Voltage:
**12V/24V With 220V
External AC Adapter**

SMLS-57

**54L PLASTIC MOBILE FRIDGE &
FREEZER DC WITH 220V POWER ADAPTER
GREY**

PRODUCT FEATURES

- ✓ Lightweight
- ✓ Shockproof Design
- ✓ Durable Plastic Handles
- ✓ Digital Temperature Controller
- ✓ Internal DC Power Supply (With 220V External AC Power Adapter)
- ✓ 2 Bottle Openers
- ✓ Cupholders On Lid
- ✓ Secure Carry Points
- ✓ Internal LED Light
- ✓ 2-Speed Setting - Turbo & Eco
- ✓ Low-Voltage Cut-Out Settings (10, 10.7, 11.8V)
- ✓ Compartment Divider (Small Compartment 5°C - 7°C Variance)
- ✓ Designed For African Conditions



SCAN FOR MORE INFO



PLEASE NOTE:

All dimensions include handles and hinges. Maintain a 150mm clearance around the unit, ensuring adequate air circulation. Avoid tilting the appliance more than 45 degrees from its upright position.

1-YEAR WARRANTY ON PARTS NOT LISTED

28

SMDZ-LS60D

**75L METAL/PLASTIC DUAL COMPARTMENT
MOBILE FRIDGE & FREEZER AC/DC
SILVER WITH BLACK TRIM**



Dimensions (mm) Unit:
(H) 461 (W) 928 (D) 470



Storage Volume: 75L
Left: **45L**
Right: **30L**



Temp Range:
-18°C to 10°C



Net Weight:
30.4Kg



Compressor:
55W



Rated Current:
12V: **4.58A**
220V: **0.35A**



Insulation:
Cyclopentane



Voltage:
**12V/24V With 220V
External AC Adapter**

- ✓ Dual Compartment
- ✓ Shockproof Design
- ✓ Durable Plastic Handles
- ✓ Multidirectional Lids (Removable)
- ✓ Digital Temperature Controller
- ✓ Internal 12V DC Power Supply (With 220V External AC Power Adapter)
- ✓ 12V DC Power Supply Conveniently Located On Both Sides of Fridge/Freezer
- ✓ Internal LED Light
- ✓ 2-Speed Setting - Max & Eco Mode
- ✓ Low-Voltage Cut-Out Settings (10, 10.7, 11.8V)
- ✓ Drainage Points
- ✓ 2 x Baskets Included
- ✓ Designed For African Conditions

PRODUCT FEATURES

29

PLEASE NOTE:
All dimensions include handles and hinges. Maintain a 150mm clearance around the unit, ensuring adequate air circulation. Avoid tilting the appliance more than 45 degrees from its upright position.

1-YEAR WARRANTY ON PARTS NOT LISTED



SCAN FOR MORE INFO





ACCESSORIES



SMACC

001

12V BATTERY CLAMP CONNECTOR

- ✓ 12V Battery Clamp Connector
- ✓ AMP Rating: 15A



Packaged Dimensions (mm):
(H) 147 (W) 127 (D) 39



Voltage:
12V DC



Net Weight:
0.1Kg



Compatibility:
**Compatible With Most
Mobile Fridge & Freezers**



Scan QR Code
For More Details
& Compatibility
Information



SMACC

002

12V ANDERSON PLUG

- ✓ 12V Anderson Plug
- ✓ Voltage Rating: 12V



Packaged Dimensions (mm):
(H) 120 (W) 80 (D) 18



Voltage:
12V DC



Net Weight:
0.035Kg



Compatibility:
**Compatible With Most
Mobile Fridge & Freezers**



Scan QR Code
For More Details
& Compatibility
Information



SMACC

003

12V DC CABLE WITH 90 DEGREE CIGARETTE LIGHTER PLUG

- ✓ Leisure Series (Plastic Range)
- ✓ 12V DC Cable with 90 Degree Cigarette Lighter Plug



Packaged Dimensions (mm):
(H) 208 (W) 138 (D) 56mm



Voltage:
12V DC



Net Weight:
0.23Kg



Compatibility:
**Scan QR Code To
Check Compatibility**



Scan QR Code
For More Details
& Compatibility
Information



SMACC 004

12V DC CABLE WITH STRAIGHT CIGARETTE LIGHTER PLUG

- ✓ Leisure Series (Plastic Range)
12V DC Cable With Straight
Cigarette Lighter Plug



Packaged Dimensions (mm):
(H) 208 (W) 138 (D) 60mm



Voltage:
12V DC



Voltage Rating: 12V
Lead Length: 2500mm



Net Weight:
0.25Kg



Compatibility:
Scan QR Code To
Check Compatibility



Scan QR Code
For More Details
& Compatibility
Information



SMACC 005

12V DC CABLE WITH ANDERSON PLUG

- ✓ Leisure Series (Plastic Range) 12V DC Cable With Anderson Plug



Packaged Dimensions (mm):
(H) 208 (W) 138 (D) 52



Voltage:
12V DC



10A Fuse In Cable
Voltage Rating: 12V
Lead Length: 2500mm



Net Weight:
0.245Kg



Compatibility:
Scan QR Code To
Check Compatibility



Scan QR Code
For More Details
& Compatibility
Information



SMACC 006

12V DC CABLE WITH ANDERSON PLUG

- ✓ Expedition Series (Stainless Steel Range) 12V DC Cable With Anderson Plug



Packaged Dimensions (mm):
(H) 233 (W) 122 (D) 46



Voltage:
12V DC



Voltage Rating: 12V
Lead Length: 2000mm



Net Weight:
0.22Kg



Compatibility:
Scan QR Code To
Check Compatibility



Scan QR Code
For More Details
& Compatibility
Information



**12V DC CABLE WITH CIGARETTE
LIGHTER PLUG**

SMACC
007

- ✓ Expedition Series (Stainless Steel Range) 12V DC Cable With Cigarette Lighter Plug



Packaged Dimensions (mm):
(H) 233 (W) 122 (D) 45



Voltage:
12V DC

- ✓ Voltage Rating: 12V
- ✓ Lead Length: 2000mm



Net Weight:
0.21Kg



Compatibility:
Scan QR Code To
Check Compatibility



Scan QR Code
For More Details
& Compatibility
Information



**12V AC & DC POWER
SUPPLY ADAPTER**

SMACC
008

- ✓ Leisure Series (Plastic Range) 12V AC & DC Power Supply Adapter



Packaged Dimensions (mm):
(H) 208 (W) 138 (D) 53



Voltage:
12V DC

- ✓ Input Voltage: 100-240V
- ✓ Output Current: 6A



Net Weight:
0.545Kg



Compatibility:
Scan QR Code To
Check Compatibility



Scan QR Code
For More Details
& Compatibility
Information



**12V BATTERY
BOX**

SMACC
009

- ✓ 12V DC Accessory Socket
- ✓ Digital Voltmeter
2 x 5 Total 3.1A
(1A / 2.1A) USB Sockets
- ✓ 16 Amp Resettable
Circuit Breaker Switch
- ✓ Positive (+) And Negative (-)
External Terminals

- ✓ Tie Down Strap
- ✓ 2 x 50 Amp Heavy Duty
Connectors (60 Amp Fuse)
- ✓ Holds Batteries Up To 110 Ah



Assembled Dimensions (mm):
(H) 200 (W) 325 (D) 185



Scan QR Code
For More Details
& Compatibility
Information

WARRANTY

TERMS & CONDITIONS

SnoMaster warrants to the 'end-user' that their products are free from defects in material workmanship, for the period prescribed below, commencing from the date of purchase. SnoMaster will repair or replace a product that develops a fault within the prescribed period of time, as set out below. **This period will commence from the date the 'end-user' purchases the product.**

220 VOLT APPLIANCES: **2 YEAR WARRANTY**

12 VOLT APPLIANCES: **3 YEAR WARRANTY**

This applies to all new SnoMaster models effective immediately. A list of applicable appliances is available to the end-user upon request. All SnoMaster appliances are covered by the warranty specified on their individual packaging, user manual, or as advertised on the SnoMaster website (www.snomaster.co.za).

All current SnoMaster appliances will continue to carry the stated warranty on their packaging, manuals, and website listings, and these will remain unchanged until further notice.

GENERAL WARRANTY TERMS AND CONDITIONS

- The warranty is only valid upon presentation of the proof of purchase consisting of the original invoice or sales slip indicating the date of purchase, accredited dealer/retailers name, model and serial number of the product. SnoMaster reserves the right to refuse warranty if this information has been removed or changed after the original purchase of the product from the accredited dealer/retailer.
- Products that are deemed to be 'portable', such as counter-top units, portable fridge/freezers and portable ice-makers will only carry a 'walk-in' warranty, whereby the product will need to be taken into the SnoMaster Service Centre, accredited service agent or accredited dealer/retailer where the product was originally purchased from.
- Products that are deemed to be 'built-in' will be repaired on site, within reason and within 50km of major cities, within South Africa only. Products that fall outside of major cities within South Africa will only carry a parts warranty or carry a call-out fee, payable in advance to SnoMaster or its accredited service agent.
- In accordance with the Consumer Protection Act, within the first six (6) months from the date of purchase, if a product fails to meet the required standards of quality, durability, and safety, SnoMaster reserves the right to inspect the product to verify the defect within 14 (fourteen) working days before approving a remedy.
- Remedies during this period may include repair or replacement of the product, at SnoMaster's discretion, provided the product is returned to an accredited dealer, retailer, or SnoMaster service center. Refunds will only be considered under exceptional circumstances and are subject to SnoMaster's approval. After the initial six (6) months, and for the remainder of the warranty period, SnoMaster's primary obligation will be to assess and repair the product. SnoMaster will not be responsible for warranty claims where defects arise from misuse, neglect, or unauthorised modifications, as outlined in the exclusions of this policy.

After 6 (six) months from the date of purchase, this warranty does not apply to any accessories, loose glass, glass doors and enameled surfaces, filters, handles, doors, lids shelving, baskets, seals or any accessories and other parts subject to wear and tear, discolouring or rust. Damage caused by abrasive and highly concentrated cleaners will void the warranty.

Important Note: To protect your product during transport for warranty-related returns or repairs, we recommend retaining the original packaging and all included accessories for at least seven (7) days. If the original packaging is not available, the customer is responsible for ensuring the product is securely packaged to prevent damage during transit. SnoMaster cannot be held liable for damage occurring as a result of insufficient or inadequate packaging, and such damage may affect the warranty claim. SnoMaster reserves the right to refuse a warranty claim if the product is damaged during transit due to inadequate packaging provided by the customer.

The warranty on the product is supplied on condition that any warranty repairs will only be carried out by a SnoMaster authorised service agent/center. SnoMaster shall not be held liable for any reimbursements, claims, damages or loss that may result from the unauthorised repair of the product. In regions or areas where SnoMaster does not have an accredited service agent, SnoMaster reserves the right to collect the appliance for repair at either its Johannesburg or Cape Town Service Centre. The customer is responsible for securely packaging the appliance for safe transportation. SnoMaster will arrange and manage the logistics of the upliftment and repair process to ensure minimal inconvenience.

The warranty conditions are only valid within the borders of South Africa. The Customer Protection Act (CPA) does not apply to cross-border countries as mentioned in the above warranty conditions. For cross-border customers (outside of South Africa), SnoMaster provides a parts-only warranty, subject to reasonable availability and stock levels.

All replacement parts must be collected from SnoMaster's head office by the customer or a courier arranged by the customer, as SnoMaster does not deliver parts or offer cross-border shipping. It is the sole responsibility of the customer to ensure that the correct parts or spares are ordered, and SnoMaster will not be held liable for incorrect parts ordered by the customer. Once the parts are collected, either by the customer or their courier, SnoMaster relinquishes all responsibility for loss, damage, or mishandling of the parts. Additionally, SnoMaster will not be liable for any damage to parts that occurs during transit after collection.

Repair or replacement carried out under the terms of this warranty does not entitle the customer to an extension, renewal, or restart of the original product's warranty period. At the discretion of SnoMaster or its authorised service agents, repairs may be completed using functionally equivalent service exchange units.

All repairs performed by SnoMaster or its authorised service agents carry a 3-month repair warranty, applicable to both labour and parts used during the completed repair. This warranty begins from the date of repair completion and applies only to the specific work carried out—it does not extend the overall product warranty or initiate a new warranty cycle. Any parts removed during the course of repair become the property of SnoMaster.

In the case of compressor replacements performed outside of the appliance's original warranty period, the replacement compressor will carry its own 1-year warranty from the date of installation. This compressor warranty applies only to the new compressor and does not affect or renew the warranty status of the rest of the appliance. All other out-of-warranty repairs will continue to carry a 3-month warranty from the date of completion.

SnoMaster is not responsible for any damage to the product arising from power irregularities, including but not limited to load shedding, power surges, voltage spikes, or other electrical anomalies. We strongly advise customers to install surge protection at the point of connection to mitigate these risks.

SnoMaster relinquishes liability for any damage, theft, or other mishaps that may occur once the product has been handed over to a third-party delivery entity (couriers, freight companies, drivers, etc.) for transportation. Once the product departs SnoMaster premises, the risk of loss or damage is transferred to the customer. We encourage customers to ensure that adequate measures are taken for the safe transportation and delivery of the product. It is the customer's responsibility to inspect all products or goods upon receipt from SnoMaster or third-party delivery services/couriers. Any visible damages, defects, shortages, or discrepancies must be reported to SnoMaster in writing within 24 hours of receipt. Failure to inspect and report such issues within this timeframe will be deemed as acceptance of the goods in their delivered condition, and SnoMaster will not be liable for claims related to visible transit damage or discrepancies thereafter.

The warranty on SnoMaster products is transferable and remains valid for the product, regardless of ownership changes. However, to process any warranty claims, the current owner must provide the original proof of purchase, including the invoice or sales slip with the date of purchase, dealer/retailer's name, and product details. The warranty remains subject to all standard terms and conditions. SnoMaster reserves the right to reject warranty claims if proof of purchase is not supplied or if the product has been misused, modified, or repaired by unauthorised service providers. The warranty provides remedies for the repair or replacement of defective products, as specified in this policy.

SnoMaster and its service agents are not liable for incidental or consequential damages arising from the use or inability to use the product, except as required by the Consumer Protection Act. This warranty does not exclude or limit any rights afforded to the consumer under the CPA.

WARRANTY EXCLUSIONS, WHERE SNOMASTER WILL NOT BE HELD LIABLE FOR DAMAGES, REPAIRS OR REPLACEMENT, INCLUDE:

- Periodic checks, maintenance, repair and replacement of parts due to normal wear and tear.
- Accidental damage due to incorrect handling, normal wear and tear, faulty installation, abuse or misuse, neglect, including but not solely limited to the failure to use the product for its intended purpose.
- Defects resulting from usage of the product in conjunction with accessories that are not approved by SnoMaster for use with the product.
- Failure of the product arising from incorrect installation or use not consistent with the instructions prescribed in the product user manual.
- Accidents, Acts of God, lightning, water, fire, public disturbances, improper ventilation, voltage fluctuations and power surges, etc.
- Unauthorised modifications carried out to the product.
- The serial number on the product has been altered, deleted, removed or made illegible.
- Any repair or tampering by an unauthorised person or attempt to repair with equipment, or use of parts not supplied by SnoMaster or authorised service agents.

The above policies are for warranty service and the customer will responsible for any costs associated with repairs that are 'specifically EXCLUDED' from the warranty conditions.

SnoMaster reserves the right to make final decisions regarding problem determination and the appropriate service option.

Exchange units assume the remaining warranty period of the original product.

The SnoMaster warranty is subject to change without any prior notice.

DEFINITIONS

220V Appliances: Refers to all SnoMaster products powered by 220V, whether used for domestic purposes (household or family use) or commercial purposes (in connection with any business or profit-generating activity).

12V Appliances: Refers to all SnoMaster portable fridge/freezers, solar panels, and accessories intended for personal use, whether in a household, family setting, or personal vehicle, for their intended purpose.

+27 11 392 5315 | info@snomaster.co.za | www.snomaster.co.za



SCAN FOR WARRANTY
INFORMATION



SnoMaster®



SnoMaster®



SnoMaster

PRODUCT CATALOGUE

ISSUE : 3

2 0 2 5 - 2 0 2 6